1-43682-K297

OMD Mk7 ModBus connector with 5 m cable

Product overview

The pre-terminated cable provides easy connection of the Modbus between the OMD Mk7 remote display unit and the control units.

The 5 m cable may be connected to an additional length of cable to connect to the control units fitted to the engine.

The cable screen and fitted ferrite core minimizes the effect of external electrical noise on system.



Details

- Pre-terminated with a 9 way D-type connector to connect to a remote display unit
- Supplied with a seal fitted to ensure an IP32 seal when connected to the remote display unit
- The cable is a two twisted pair screened (70°C) halogen free and oil resistant cable
- Unterminated end allows the cable to be trimmed to a require length

1-43682-K297

OMD Mk7 ModBus connector with 5 m cable

Technical specifications

General

Maximum operating voltage	300 V

Conductor

Cross section	0.25 mm²
No. of conductors	Two twisted pairs
Colour of conductors	Red and black, white and black

Physical

Physical dimensions	min 4.9 to max 5.1 m 300 x 300 x 30 mm (L x W x H, shipping)
Outer diameter	6.7 mm
Net weight	480 g
Shipping weight	480 g
Colour	Grey

Environmental

Operating temperature	0 to +70°C
Storage temperature	-20 to +60°C

Regulatory

Standards	IACS M10 / M67

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 21 August 2026 - 14:44